## APEWF鋼絲強化EPDM橡膠軟管

(白色EPDM内壁,彈性佳)





APEWF鋼絲強化EPDM橡膠軟管是用於更高壓力和溫度應用的優質食品飲料軟管,特別為處理大量液體食品而設計,例如酒、啤酒、飲用水、水果汁、牛奶和牛奶副產品。

APEWF鋼絲強化EPDM橡膠軟管經鋼絲螺旋強化,適合作為抽吸和排泄軟管用於各種工業中,包括製藥、生物技術和化學。 APEWF鋼絲強化EPDM橡膠軟管具有光滑衛生內壁用於非限制流動,例如沖洗站、冷卻劑輸送、乙二醇加工和其它。



### 產品特點

- 極好的抗化學性使它成為很多高要求應用中的理想用管
- 專為真空抽料與排料應用而設計
- 螺旋綱絲強化後耐受更高壓力並保持原有真空度
- 光滑衛生白色EPDM内管抗細菌集結,符合FDA標準,可用於接觸食品表面,非常合適於食品、釀酒業使用。比如應用在葡萄酒、啤酒、瓶裝水、果汁。
- 無味内管―與酒、啤酒、飲用水、水果汁、牛奶和牛奶副產品使用後仍保持純淨
- 比標準EPDM軟管處理更大範圍溫度
- 比特氟龍軟管彎曲度更好
- 用於處理CIP溶液非常理想;也可蒸汽消毒,在150°C溫度下可達30分鐘
- 指定的軟管結構設計用於更大彎曲度—易於處理彎曲、轉彎和畸角
- 抗風化、耐磨、耐脂肪光滑橡膠外壁
- 尺寸自3/4 in. (19 mm)至 4 in. I.D. (102 mm)
- 提供全套接頭扣壓
- 不銹鋼保護套在保持彎曲度的同時避免軟管壓碎、扭結、惡劣環境和摩擦的損害
- 也可訂購鐳射蝕刻不銹鋼卡套,易於快速識別
- 也可訂購軟管具有Track™ RF標識和壽命迴圈分析系統—RFID標籤唯一識別單個軟管組裝件,建立監察線索,跟蹤與磨損有關的主要事件







# APEWF鋼絲強化EPDM橡膠軟管

(白色EPDM内壁,彈性佳)





SPECIFICATIONS

貨號	内徑		壁厚		外徑		真空度		工作壓力		Bend Radius		重量 (lbs./ft.)
	(in.)	(mm)	(in.)	(mm)	(in.)	(mm)	(in. Hg)	(Bar)		F(20°C) (Bar)	(in.)	(mm)	
4 DELVE 144 0.7.5.0	7.5	10	00/	,	1.00	0.1	0 / 50		450	00	0	, ,	4.6
APEWF-W-0750	.75	19	.236	6	1.22	31	26.58	.9	450	32	2	66	.46
APEWF-W-1000	1	25	.236	6	1.46	37	26.58	.9	400	28	3	88	.56
APEWF-W-1500	1.5	38	.256	6.5	2.01	51	26.58	.9	300	20	5	135	.94
APEWF-W-2000	2	51	.275	7	2.56	65	26.58	.9	225	16	7	200	1.28
APEWF-W-3000	3	76	.295	8	3.58	91	23.62	.8	175	12	12	320	2.08
APEWF-W-4000	4	102	.335	9	4.68	119	23.62	.8	150	10	15	400	3.29

#### NOTES:

Variables that impact working pressure include the type of fluid being conveyed through the hose, its temperature, pressure, and time. Field testing is recommended. Burst pressure is greater than or equal to three times the working pressure.

Temperature range: -40°F (-40°C) up to 248°F (120°C), depending on the product being conveyed. For sterilization purposes: up to 302°F (150°C) maximum for 30 minutes.

When products are used as part of an assembly, the pressure ratings of fittings may be less than hose pressure ratings above. Please consult your sales representative.

## Purity in Fluid Flow Systems®

Address: NewAge Industries AdvantaPure®

145 James Way

Southampton, PA 18966 U.S.A.

Toll Free Phone: 888-755-4370
Phone: 215-526-2151
Toll Free Fax: 888-258-4293
Fax: 215-526-2167

Web Site: www.advantapure.com
E-mail: sales@advantapure.com

Advanta PÜRE®



DISTRIBUTED BY:

興全貿易股份有限公司 電話: 02-89413600

email: info@cintrade.com.tw

©2011 NewAge® Industries, Inc. Specifications are subject to change without notice AdvantaPure products are produced by NewAge® Industries, Inc. Hose Track®, Purity in Fluid Flow Systems®, NewAge Industries AdvantaPure®, NewAge®, and the "N" logo are trademarks of NewAge® Industries, Inc.



