

透明抗微生物無塑化劑PVC管





Fluid Transfer Specialists®



透明抗微生物無塑化劑PVC管

Clearflo[®] Ag-47.

■無毒配方製造,符合FDA標準

- 無塑化劑、乳膠、動物來源成份
 - 被美國國基衛生基金會 (NSF-51) 列入食品設備材料
 - 整條管子都是抗菌,而並非其它廠牌只有內部抗 菌而已
 - 透明可看到液體流動
 - ■含抗微生物科技,可抵抗大腸桿菌、李斯特菌、沙 門氏菌、退伍軍人症病原菌, MRSA, 曲狀桿菌、綠 膿桿菌
 - ■非常適合食品飲料應用,例如非脂飲料、牛奶、酒精性飲料(酒精濃度低於20%)
 - 可熱封口
 - 符合REACH and RoHS規範要求



Notes

CLEARFLO Ag-47 is suitable for a wide variety of food contact applications and designed to protect your food or beverage product from harmful bacteria. It's manufactured from a clear flexible Shore A74 non-phthalate PVC compound with the addition of antimicrobial protection. The antimicrobial technology is especially effective where there is infrequent use of fluids in warm or humid conditions and the tubing has no opportunity to dry thoroughly between uses.

The antimicrobial properties protect the tubing against organisms that can cause growth-based discoloration and odors. Testing has proven that the active ingredients neutralize bacteria rapidly, and because the ingredients do not dissipate with use, they can be expected to offer protection for an extended time under normal conditions. CLEARFLO Ag-47 offers antibacterial performance to ISO 22196:2011.

Unlike some products CLEARFLO Ag-47 is 100% protected with the effective additive, which is present throughout the tube and not only on the interior, offering you protection on all surfaces. This is especially important in applications where the tubing is dipped into a fluid.

The active ingredients in CLEARFLO Ag-47 will have no detrimental effect on yeasts used for brewing and will have no negative impact on the taste or flavor of products passed through it.

貨號	內徑 (IN.)	外徑 (IN.)	壁厚 (IN.)	WORKING PSI AT 70°F	BURST PSI AT 70°F	LBS. PER 100 FT.
1190014	1/8	1/4	1/16	159	478	1.95
1190021	1/8	3/8	1/8	237	710	5.19
1190035	3/16	5/16	1/16	126	379	2.59
1190049	3/16	7/16	1/8	180	540	6.48
1190112	1/4	3/8	1/16	100	301	3.25
1190126	1/4	1/2	1/8	161	482	7.79
1190189	5/16	7/16	1/16	83	248	3.89
1190203	5/16	9/16	1/8	121	364	9.08
1190266	3/8	1/2	1/16	74	223	4.55
1190280	3/8	5/8	1/8	108	324	10.38
1190343	1/2	5/8	1/16	51	154	5.85
1190357	1/2	3/4	1/8	83	249	12.98
1190392	5/8	3/4	1/16	43	130	7.14
1190399	5/8	7/8	1/8	77	232	15.58
1190448	3/4	7/8	1/16	34	101	8.44
1190455	3/4	1	1/8	68	203	18.17
1190497	1	1-1/4	1/8	53	160	23.37

Standard coil length is 100 ft. Add length suffix to part number when ordering. Example: 100 ft. of 3/16" I.D. x 5/16" O.D. tubing is part number 119 0035-100. Sold by standard coil length only.

BOLD indicates the critical dimension for fittings application.

Physical Properties**

Hardness, Shore A ±5	74
Operating Temperature Range, °F	-40 to 125
Operating Temperature Range, °C	-40 to 52

**Values listed are typical for the material used in manufacture, except where noted, and are meant only as a guide to aid in design. Field testing should be performed to find the actual values for your application.

Recommended Fittings & Clamps

- Thermobarb[®] plastic barbed fittings
- Stainless steel barbed fittings
- Oetiker[®] ear type clamps
- Kwik Clamp[™] nylon double bond hose clamps
- Worm gear clamps

Clearflo, Kwik Clamp, Thermobarb, NewAge, "Fluid Transfer Specialists," and The "N" Logo are trademarks of NewAge® Industries, Inc. • Oetiker reg, TM Oetiker, Inc

WARANT: NewAge Industries, new reget, Fluid Interface Operations, and the N Euglid are unable in the N Euglid are unables, inc. C enterfage. In the NewAge Industries are developed in the N Euglid are unables in the N Euglid are unables, inc. C enterfage. In the N Euglid are unables in the N Euglid are unables, inc. C enterfage. In the N Euglid are unables, in the N Euglid are unables, inc. C enterfage. In the N Euglid are unables, inc. C enterf

DISTRIBUTOR PARTNER



145 James Way Southampton, PA 18966 www.newageindustries.com 800-50-NEWAGE (800-506-3924) 215-526-2300 Fax: 800-837-1856 215-526-2190 info@newageindustries.com